

Mi-TIC E™



INTRODUCTION

The Mi-TIC E is the world's smallest high resolution thermal imager for fire fighting applications. The camera provides a crystal clear image with dynamic range up to 760°C (1400°F) and at the same time see very low temperature objects, which is ideal for casualty searches.

Every Mi-TIC E is supplied with a unique dual use desktop/in-truck charger station which securely retains and charges both the thermal imager and a spare battery. The charger stations can be daisy-chained together, up to a maximum of 6 units.

PERSONAL

Weighing approximately 750g (26oz) the Mi-TIC E is a small format thermal imager that can be easily and comfortably held in the palm of your hand. Unlike many thermal imagers, the Mi-TIC E design allows it to be worn in multiple ways – in the hand, inside a pocket, clipped outside a pocket, clipped to a lanyard or hung around the neck.

SIMPLE

With a thumb operated green on/off button and superb start up time of 5 seconds, the Mi-TIC E is simple to use.

SAFE

The Mi-TIC E has Class I, Division 2 Non Incendive certification. The use of Lithium Iron Phosphate technology ensures the Mi-TIC E delivers 3 hours of battery life over 1,000s of cycles. They are inherently safe due to the use of patented nanophosphate® technology.



CAMERA STANDARD FEATURES

The Mi-TIC E comes with the most advanced features available in any thermal imaging camera. These include:

2.7" LCD Display	Image Capture (1000 images)*
Direct Temperature Measurement (DTM)	X2 and X4 Digital Zoom*
Tri-Mode Sensitivity	Video Capture (16 hours) including 'Black Box' recording
Customisable start-up screen	Image Freeze*
Firefighting application modes* <ul style="list-style-type: none"> • Fire mode • Overhaul • Size Up • Inspection 	User Replaceable Germanium window (Order code: ARG_MI_RWS)
Search and Rescue application modes* <ul style="list-style-type: none"> • White Hot 	No PC Software required for image and video download – when the camera is docked, it is recognised as a removable device, like a USB memory stick

* 3-button variants only

CAMERA STANDARD ACCESSORIES

The Mi-TIC E comes with the following accessories as standard:

Two Mi-TIC Lithium Iron Phosphate Battery Pack. (Yellow) (Order code: ARG_MI_BLPYN-2)	USB Connection Lead for connecting dock to PC / Laptop. (Order code: ARG_MI_USB)
Truck/Desktop Charger Dock with mains plug and universal mounting plate. (US, UK, Europe, Aus and South America). (Order code: ARG_MI_CS)	Pocket Clip. (Order code: ARG_MI_PCLIP)
Retractable Lanyard. (Order code: ARG_MI_RL)	Quick Start Guide

CAMERA OPTIONAL ACCESSORIES

argus® Mi-TIC Black Hard Case. (Order code: ARG_MI_BHC)	argus® Neck Strap. (Order code: P7030NS)
argus® Mi-TIC Sunshroud. (Order code: ARG_MI_SS)	AA Battery Pack. (Order code: ARG_MI_YAA)
argus® Soft Carry Case. (Order code: P7030SC)	

CAMERA ORDER CODES

Code	Resolution	Buttons	Frame rate
MI-320-1-E	320x240	1	30Hz
MI-329-1-E	320x240	1	9Hz
MI-320-3-E	320x240	3	30Hz
MI-329-3-E	320x240	3	9Hz

WARRANTY

3 year Camera Warranty
5 year Battery Warranty
10 year Focusing Lens and Sensor Warranty

ENVIRONMENTAL DATA

Thermal conditions The camera has been designed to operate:

- continuously between -20°C (-4°F) and +85°C (185°F) or
- 150°C (300°F) for 15 minutes
- 260°C (500°F) for 5 minutes

Sealing	IP67, will withstand immersion in water
Impact	The camera will withstand a drop from a height of 2m (78 inches) onto concrete
Storage	It is recommended that for maximum effective operational life, the storage temperature is kept between -20°C (-4°F) and +40°C (104°F)

OPTICAL DATA

Detector	
Sensor type	Un-cooled Microbolometer
Sensor material	Amorphous Silicon (ASi)
Resolution	384 x 288px
Pixel size	25µm
Spectral response	7.5 – 14µm
MDTD (Full camera system sensitivity)	60mK (0.06°C) typical (Minimum Discernible Temperature Difference)
NETD (Sensor sensitivity)	<50mK (<0.05°C)
Dynamic range	-40°C to 760°C (-40°F to 1400°F)
Refresh rate	60Hz
Direct Temperature Measurement (DTM)	-40°C to 760°C (-40°F to 1400°F)
Lens	
Lens material	Germanium Composite
Focal length	1m to infinity, optimised at 4m (3ft to infinity, optimised at 13ft)
Aperture	f/1.0
Field of view	50° horizontal, 37.5° vertical, 62° diagonal
Display	
Type	High grade, Industrial, colour TFT active matrix LCD
Size	69mm (2.7 inches)
Pixel format	QVGA 320 x 240, (each pixel RGB format, total pixels 230,400 pixels)
Video input	Sensor synchronised direct digital drive
Backlight	400cd/m ²

MECHANICAL DATA

Camera dims (H x W x D)	203mm x 96mm x 71mm (8 x 3 ³ / ₄ x 2 ¹³ / ₁₆ inches)
Camera weight	600g (21oz) without battery 765g (27oz) with standard battery 855g (30oz) with high capacity battery
Battery dims (H x W x D)	87mm x 76mm x 28mm (standard battery) 87mm x 76mm x 35mm (high capacity battery)
Battery weight	165g (6oz) standard battery 255g (9oz) high capacity battery
Charger dims (H x W x D)	167mm x 112mm x 120mm
Charger weight	550g (1lb 3oz)
Main camera body	Radel®R-5100 and Santoprene®
LCD window	Ultrason® E 2010 HC
LCD bumper	Santoprene®
Ge Window collar	Radel®R-5100 and Santoprene®
Lens window	Germanium (2mm thick) with durable coating

ELECTRICAL DATA

Power consumption	<3 W typical
Start-up time	5 seconds typical
Battery type	Lithium Iron Phosphate Rechargeable Battery
Battery capacity	1500 mAh, 6.6V (standard battery) 2500mAh, 6.6V (high capacity battery)
Std Battery life	In excess of 3 hours @ ambient temperature (22°C, 72°F)
Std Battery charge time	Less than 3 hours
High Capacity Battery Life	In excess of 5 hours @ ambient temperature (22°C, 72°F)
High Cap, Battery charge time	Less than 4.5 hours
Battery recharge cycles	Over 2000 cycles
Battery charging temp.	5°C to 40°C (41°F to 104°F)
Charger input voltage	11V – 30V DC (12V and 24V vehicle systems)
Charger operating temp.	0°C to 40°C (32°F to 104°F)

COMPLIANCE DATA

Performance	NFPA 1801:2013 Standard on Thermal Imagers for Fire Services
Safety	IEC 60950-1:2005+A1:2009+A2:2013 and related national standards (T _{amb} +80°C max) ANSI/ISA 12.12.01:2007 Class I, Division 2, Groups C, D T4, -25°C (-13°F) to +70°C (158°F)
Emissions RFI/EMC	BS EN 61000-6-3:2007 + A1:2011, BS EN 50498:2010, ICES-003(2012), FCC CFR-47 Subpart B, AUS/NZ 4251.1
Immunity	BS EN 61000-6-2:2005, BS EN 50498:2010
Vibration/Shock	BS EN 60721-3-2 Class 2M3
RoHS	All parts of the system are compliant with EU directive 2011/65/EC

Avon Protection and Avon Protection Systems are trading names of Avon Rubber p.l.c. (registered in England with number 32960). The Avon name and logo is the registered trademark of Avon Rubber p.l.c.
© Avon Rubber p.l.c 2018.