



DUO SAFETY LADDER CORPORATION

Aluminum Roof Ladder with Roof Hooks on both ends



Channel Rail construction provides the advantage of extra strength without cumbersome weight. This ladder is designed for firefighters so that no matter which end of the ladder is on top, there are hooks available. Furnished with standard 3/4" hooks or heavy duty 7/8" hooks for an additional fee. **Please note: this product is made to order and not returnable.**

Series 775-DR

Series 875-DR

- Channel Rail Construction
- 750lb Duty Rated

SPECIFICATIONS

SERIES 775-DR DOUBLE END ROOF

| Size | Closed Length | Width | Rail Size | Weight |
|------|---------------|-------|-----------|--------|
| 10' | 10' 1.625" | 19" | 2.75" | 29 lbs |
| 12' | 12' 1.625" | 19" | 2.75" | 33 lbs |
| 14' | 14' 1.625" | 19" | 2.75" | 35 lbs |

SERIES 875-DR DOUBLE END ROOF

| Size | Closed Length | Width | Rail Size | Weight |
|------|---------------|-------|-----------|--------|
| 16' | 16' 2.125" | 19" | 3.25" | 49 lbs |
| 18' | 18' 2.125" | 19" | 3.25" | 53 lbs |
| 20' | 20' 2.125" | 19" | 3.25" | 56 lbs |

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard
Rubber safety shoes optional for hard surface use.

920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com
Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

