



# DUO SAFETY LADDER CORPORATION

## Aluminum Roof Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. Ideal for pumper use - these outstanding ladders have been proven and approved for many years by fire companies everywhere. Installed with standard 3/4" hooks or heavy duty 7/8" hooks for an additional fee.



### Series 775-A

### Series 875-A

### Series 1275-A

- Channel Rail Construction
- 750lb Duty Rated

#### SPECIFICATIONS

##### SERIES 775-A ROOF

Size	Closed Length	Width	Rail Size	Weight
10'	10' 2.25"	19"	2.75"	22 lbs
12'	12' 2.25"	19"	2.75"	24 lbs
14'	14' 2.25"	19"	2.75"	28 lbs

##### SERIES 875-A ROOF

Size	Closed Length	Width	Rail Size	Weight
16'	16' 2.5"	19"	3.25"	39 lbs
18'	18' 2.5"	19"	3.25"	44 lbs
20'	20' 2.5"	19"	3.25"	48 lbs

##### SERIES 1275-A ROOF

Size	Closed Length	Width	Rail Size	Weight
25'	25' 3"	19"	3.75"	64 lbs
30'	30' 3"	19"	3.75"	72 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard  
Rubber safety shoes optional for hard surface use.

---

**920-231-2740    fax 920-231-2460    mail@duosafety.com    www.duosafety.com**  
**Duo-Safety Ladder Corporation    513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497**

---