



DUO SAFETY LADDER CORPORATION



Aluminum Wall Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. Ideal for pumper use - these outstanding ladders have been proven and approved for many years by fire companies everywhere.

Series 750-A

Series 850-A

Series 1250-A

- Channel Rail Construction
- 750lb Duty Rated

SPECIFICATIONS

SERIES 750-A WALL

Size	Closed Length	Width	Rail Size	Weight
8'	8' 2.25"	19"	2.75"	14 lbs
10'	10' 2.25"	19"	2.75"	17 lbs
12'	12' 2.25"	19"	2.75"	20 lbs
14'	14' 2.25"	19"	2.75"	25 lbs

SERIES 850-A WALL

Size	Closed Length	Width	Rail Size	Weight
16'	16' 2.5"	19"	3.25"	35 lbs
18'	18' 2.5"	19"	3.25"	43 lbs
20'	20' 2.5"	19"	3.25"	45 lbs

SERIES 1250-A WALL

Size	Closed Length	Width	Rail Size	Weight
25'	25' 3"	19"	3.75"	62 lbs
30'	30' 3"	19"	3.75"	70 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard
Rubber safety shoes optional for hard surface use.

920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com
Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497
