



# DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

- Home
- Contact
- Warranty
- History
- FAQ

- PRODUCTS
- REPLACEMENT PARTS
- PRICE LIST
- LADDER MAINTENANCE
- NEWS / INFORMATION
- FREIGHT ESTIMATES

## Aluminum Tubular Rail Fire Ladders

The tubular construction of Duo-Safety's 500-C Series incorporates the inherent strength of a rectangle, a channel and an "I" beam combined to provide the ultimate in strength and safety. Construction features include: double parallel fins; double set of truss plates; ribbed, extruded rungs, electrically welded to outside of truss plates; and aluminum rivets. See our [Price List](#) for current pricing.



Series 550-C



Series 575-C

### Series 550-C Wall Series 575-C Roof

- 750lb Duty Rated


#### SPECIFICATIONS SERIES 550-C Wall

Size	Closed Length	Width	Banking Thickness	Weight
10'	10' .5"	22.5"	4.5"	31 lbs
12'	12' .5"	22.5"	4.5"	37 lbs
14'	14' .5"	22.5"	4.5"	44 lbs
16'	16' .5"	22.5"	4.5"	48 lbs
18'	18' .5"	22.5"	4.5"	55 lbs
20'	20' .5"	22.5"	4.5"	59 lbs
22'	22' .5"	22.5"	4.5"	67 lbs
24'	24' .5"	22.5"	4.5"	74 lbs
25'	25' .5"	22.5"	4.5"	77 lbs
26'	26' .5"	22.5"	5.5"	81 lbs
28'	28' .5"	22.5"	5.5"	88 lbs
30'	30' .5"	22.5"	5.5"	96 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

#### SPECIFICATIONS SERIES 575-C Roof

Size	Closed Length	Width	Banking Thickness	Weight
------	---------------	-------	-------------------	--------



## Duo-Safety Ladder Products

10'	10' .5"	19.75"	4.5"	39 lbs
12'	12' .5"	19.75"	4.5"	43 lbs
14'	14' .5"	19.75"	4.5"	50 lbs
16'	16' .5"	19.75"	4.5"	55 lbs
18'	18' .5"	19.75"	4.5"	57 lbs
20'	20' .5"	19.75"	4.5"	63 lbs
25'	25' .5"	19.75"	4.5"	80 lbs
30'	30' .5"	19.75"	5.5"	100 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

---

Prong feet as Standard  
Rubber safety shoes optional for hard surface  
use.

---



[Printer Friendly](#)

**Duo-Safety Ladder Corporation** 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497  
920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com