



DUO SAFETY LADDER CORPORATION

Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks, or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

Series 1200-A

Series 1225-A

- 3-3/4" Channel Rail
- 750lb Duty Rated



Two Section
Series 1200-A



Three Section
Series 1225-A

SPECIFICATIONS

SERIES 1200-A 2-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
28'	16' 3.25"	24"	6.5"	87 lbs
30'	18' 3.25"	24"	6.5"	107 lbs
35'	20' 3.25"	24"	6.5"	122 lbs

SERIES 1225-A 3-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
28'	12' 11"	24"	9.125"	107 lbs
30'	13' 3"	24"	9.125"	108 lbs
35'	15' 3"	24"	9.125"	129 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard
Rubber safety shoes optional for hard surface use.

920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com
Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497