



DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

[Home](#) [Contact](#) [Warranty](#) [History](#) [FAQ](#)

PRODUCTS

REPLACEMENT PARTS

PRICE LIST

LADDER MAINTENANCE

NEWS / INFORMATION

FREIGHT ESTIMATES



Request A Catalog



14" Rung Centers

Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks, or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid. See our [Price List](#) for current pricing.

Series 1500-A Series 1525-A

- 5" Channel Rail
- 750lb Duty Rated

SPECIFICATIONS

SERIES 1500-A 2-SECTION WITH POLES

Size	Closed Length	Width Over Poles	Banking Thickness	Weight With Poles
40'	23' 4"	*26.5"	7.4"	213 lbs
45'	26' 4"	26.5"	7.4"	242 lbs

SERIES 1525-A 3-SECTION WITH POLES

Size	Closed Length	Width Over Poles	Banking Thickness	Weight With Poles
40'	16' 10"	*26.5"	9.8"	215 lbs
45'	19'	26.5"	9.8"	240 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

*Staypoles are optional on 40ft length
Base width is 24" standard plus 2-1/2" to go overpoles
Weight without poles deduct approx. 35 lbs each

All Extension ladders 40ft and over are equipped with 1/2" manila rope as standard

Prong feet as Standard
Rubber safety shoes optional for hard surface use.

[Series 1000-A](#) | [Series 900-A](#) | [Series 912](#) | [Series 1200-A](#) | [Series 1500-A](#)





Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497
920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com