



# DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

[Home](#)
[Contact](#)
[Warranty](#)
[History](#)
[FAQ](#)
[PRODUCTS](#)
[REPLACEMENT PARTS](#)
[PRICE LIST](#)
[LADDER MAINTENANCE](#)
[NEWS / INFORMATION](#)
[FREIGHT ESTIMATES](#)


Request A Catalog



Three Section  
Series 912

## Solid Beam Aluminum Ladders

These ladders were originally produced for the Forestry Departments for use on their brush pumpers. This ladder was designed for a maximum closed length to fit in a restricted space. Due to the compact design, this ladder does not have a cable pulley to help extend the fly section. In order to extend the ladder, you must first extend the fly section by hand and use the rope and pulley to fully extend the ladder. See our [Price List](#) for current pricing.

### Series 912

- 3-1/4" Channel Rail
- 750lb Duty Rated

#### SPECIFICATIONS

##### SERIES 912-86 3-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
16'	86"	24"	8.125"	65 lbs

##### SERIES 912-100 3-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
20'	100"	24"	8.125"	80 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard  
Rubber safety shoes optional for hard surface use.

[Series 1000-A](#) | [Series 900-A](#) | [Series 912](#) | [Series 1200-A](#) | [Series 1500-A](#)



[Printer Friendly](#)

Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497  
920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com