



DUO SAFETY LADDER CORPORATION

Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks, or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

Series 1000-A

- 2-3/4" Channel Rail
- 750lb Duty Rated



Two Section
Series 1000-A

SPECIFICATIONS

SERIES 1000-A 2-SECTION

Size	Closed Length	Width	Banking Thickness	Weight
10'	7' 2.25"	18.5"	4.56"	29 lbs
12'	8' 2.25"	18.5"	4.56"	32 lbs
14'	9' 2.25"	18.5"	4.56"	34 lbs
16*	9' 11.5"	18.5"	4.56"	40 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

*Rope and pulley installed standard on 16' length only.
Shorter lengths raised by hand.

