



DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

[Home](#) [Contact](#) [Warranty](#) [History](#) [FAQ](#)

PRODUCTS

REPLACEMENT PARTS

PRICE LIST

LADDER MAINTENANCE

NEWS / INFORMATION

FREIGHT ESTIMATES



Request A Catalog



Two Section
Series YGE-2

Fiberglass Solid Side Ladders

Fire ladders using extruded fiberglass channel rail construction and aluminum rungs welded to aluminum blocks and riveted to the fiberglass side rails.

All fiberglass ladders are non-conductive for single phase 110 volt service with a maximum of 30,000 volts only. Dependent upon conditions. See our [Price List](#) for current pricing.

Series YGE-2

Series YGE-3

- 4-1/2" Channel Rail
- 750lb Duty Rated
- Special self-extinguishing resin - will not support flame
- Special high temperature resins for heat resistance
- Special ultra-violet screen for fade resistance
- Safety yellow color for better visibility in smoke



Three Section
Series YGE-3

SPECIFICATIONS

SERIES YGE-2 2-SECTION EXTENSION

Size	Closed Length	Width	Banking Thickness	Weight
16'	10' .5"	23"	7"	80 lbs
20'	12' 3.5"	23"	7"	95 lbs
24'	14' 3.5"	23"	7"	110 lbs
28'	16' 3.5"	23"	7"	126 lbs
30'	17' 10.5"	23"	7"	140 lbs
35'	20' 3.5"	23"	7"	160 lbs

SPECIFICATIONS

SERIES YGE-3 3-SECTION EXTENSION

Size	Closed Length	Width	Banking Thickness	Weight
28'	12' 11.5"	26.5"	9.5"	162 lbs
30'	13' 3.5"	26.5"	9.5"	170 lbs
35'	15' 3.5"	26.5"	9.5"	195 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard
Rubber safety shoes optional for hard surface use.



[Printer Friendly](#)

