



# DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

- [Home](#)
- [Contact](#)
- [Warranty](#)
- [History](#)
- [FAQ](#)

- PRODUCTS
- REPLACEMENT PARTS
- PRICE LIST
- LADDER MAINTENANCE
- NEWS / INFORMATION
- FREIGHT ESTIMATES

## Aluminum Tubular Rail Fire Ladders

The 500-C Series ladders represent great strength and extraordinary safety. All this is incorporated into the tubular rail construction of this ladder. Available in all standard sizes - see specifications below. See our [Price List](#) for current pricing.

- Series 500-C**
- Series 525-C**
- 750lb Duty Rated



Series 500-C Truss Ladder



Request A Catalog

### SPECIFICATIONS

#### SERIES 500-C 2-SECTION

Size	Closed Length	Width	Width Over Poles	Banking Thickness	Weight
14'	9' .75"	24"		7"	74 lbs
16'	10' .75"	24"		7"	75 lbs
18'	11' .75"	24"		7"	76 lbs
20'	12' .75"	24"		7"	78 lbs
24'	14' .625"	24"		7"	90 lbs
28'	16' .625"	24"		8"	112 lbs
30'	18' .75"	24"		8"	131 lbs
35'	20'	24"		8"	153 lbs
40'	23' .75"	24"	26"	8"	210 lbs
45'	26' .75"	24"	26"	9"	255 lbs
50'	28' .75"	24"	26"	9"	279 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

### SPECIFICATIONS

#### SERIES 525-C 3-SECTION

Size	Closed Length	Width	Width Over Poles	Banking Thickness	Weight
28'	13' .75"	26"		10.25"	140 lbs
30'	14' .75"	26"		10.25"	164 lbs
35'	15' 4"	26"		10.25"	179 lbs
40'	17' 7.75"	26"	28.5"	10.25"	245 lbs
45'	19' .75"	26"	28.5"	11.25"	265 lbs

50' 21' 2.75" 26" 28.5" 11.25" 297 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

---

\*Staypoles are optional on 40ft length  
Weight without poles deduct approx. 35 lbs each

All Extension ladders 40ft and over are equipped  
with 1/2" manila rope as standard

Prong feet as Standard  
Rubber safety shoes optional for hard surface use.

---



[Printer Friendly](#)

 **Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497**  
920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com