



DUO SAFETY LADDER CORPORATION

"Use A Good Ladder Or Stay On The Ground"

[Home](#)
[Contact](#)
[Warranty](#)
[History](#)
[FAQ](#)
[PRODUCTS](#)
[REPLACEMENT PARTS](#)
[PRICE LIST](#)
[LADDER MAINTENANCE](#)
[NEWS / INFORMATION](#)
[FREIGHT ESTIMATES](#)


Request A Catalog



Series YGW

Fiberglass Fire Ladders

Fire ladders using extruded fiberglass channel rail construction and aluminum rungs welded to aluminum blocks and riveted to the fiberglass side rails.

All fiberglass ladders are non-conductive for single phase 110 volt service with a maximum of 30,000 volts only, dependent upon conditions. See our [Price List](#) for current pricing.

Series YGW-Wall

- 3-3/8" Channel Rail
- 750lb Duty Rated
- Special self-extinguishing resin - will not support flame
- Special high temperature resins for heat resistance
- Special ultra-violet screen for fade resistance
- Safety yellow color for better visibility in smoke

SPECIFICATIONS

SERIES YGW-Wall

Size	Closed Length	Width	Banking Thickness	Weight
10'	10' 2.5"	19.25"	3.375"	26 lbs
12'	12' 2.5"	19.25"	3.375"	30 lbs
14'	14' 2.5"	19.25"	3.375"	36 lbs
16'	16' 2.5"	19.25"	3.375"	40 lbs
18'	18' 2.5"	19.25"	3.375"	46 lbs
20'	20' 2.5"	19.25"	3.375"	50 lbs

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

[Fiberglass Roof Ladders](#) | [Fiberglass Wall Ladders](#)



[Printer Friendly](#)



Duo-Safety Ladder Corporation 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497
920-231-2740 fax 920-231-2460 mail@duosafety.com www.duosafety.com